

Visilink Bullet KPF 120R-VF



Camera	
Image Sensor	1/2.7" CMOS
Effective Pixels	1920(H)×1080(V), 2MP
Scanning System	Progressive
Electronic Shutter Speed	PAL: 1/25~1/100000s NTSC: 1/30~1/100000s
Minimum Illumination	0.02Lux/F1.3, 30IRE, 0Lux IR on
S/N Ratio	More than 65dB
IR Distance	Up to 60m
IR On/Off Control	Auto / Manual
IR LEDs	4
Lens	
Lens Type	Vari-focal lens / Fixed iris
Mount Type	Board-in
Focal Length	2.7-13.5mm
Max Aperture	F1.3
Angle of View	H: 106°~30°
Focus Control	Manual
Close Focus Distance	200mm
DORI Distance	
Detect	Wide 45m / Tele 148m
Observe	Wide 18m / Tele 59m
Recognize	Wide 9m / Tele 30m
Identify	Wide 5m / Tele 15m
Pan / Tilt / Rotation	
Pan/Tilt/Rotation	Pan: 0° ~ 360° Tilt: 0° ~ 87° Rotation: 0° ~ 360°
Video	
Resolution	1080P (1920×1080)
Frame Rate	25/30fps@1080P, 25/30/50/60fps@720P
Video Output	1-channel BNC high definition video output / CVBS video output
Day/Night	Auto (ICR) / Manual
OSD Menu	Multi-language
BLC Mode	BLC / HLC / DWDR
WDR	DWDR
Gain Control	AGC
Noise Reduction	2D
White Balance	Auto / Manual
Smart IR	Auto / Manual
Electrical	
Power Supply	12V DC ±25%
Power Consumption	Max 7.9W (12V DC, IR on)
Environmental	
Operating Conditions	-40°C ~ +60°C
Ingress Protection & Vandal Resistance	IP67
Construction	
Casing	Aluminium
Dimensions	213.0mm×90.4mm×90.4mm
Net Weight	0.55kg
Gross Weight	0.68kg